

879 Sparkling Silver Glitterflake



Overview: Glitterflakes are commonly used to repair damaged bass boats or to make any project stand out from the crowd! Glitterflakes are .015" polyester flakes compatible with out #173 Gel Coat. By applying a layer of Clear into the mold followed by Clear with glitterflake, a metallic look is achieved. Typically glitterflake is backed with a pigmented layer to opaque the fiberglass reinforcement. Glitterflake may be used with the regular gel coat spray equipment. A nozzle of .015" is recommended.

Available in 4 oz., 1lb., 4lb., and 10lb. containers

Mixing Directions: Mix approximately 10-20% Glitterflake by weight with the Clear Gel Coat. At higher than 20% the Glitterflake may retard the Gel Coat. In order to provide a total hide, it is recommended that a pigmented layer be used directly behind the Glitterflake.

Storage: Keep out of reach of children. Glitterflake should be stored in a closed container at room temperature. Refer to MSDS Sheet for further instructions.

Safety and Handling: #879 Sparkling Silver Glitterflake poses no unique hazard by itself but should be used in a well ventilated area or with adequate respiratory protection whenever combining with gel coat. Glitterflake is easily suspended into the air and you may find that it travels quickly to unwanted areas. Use paper mixing and measuring tools instead of plastic or metal. Contact with skin and eyes should be avoided and necessary protective equipment and clothing should be worn. Individuals should wash with soap and water before eating, drinking, or using toilet facilities. Individuals should observe conditions of good industrial hygiene and safe working practices. For more detailed instructions on handling please refer to the MSDS Sheet.